

D400 SEVERN

Hinged



SEVERN 450 S



BUFFALO

Features:

- Manufactured to BS EN 124 class D400
- BSI Kitemarked for third party assurance of quality
- Products comply with CD 534
- Products comply with BS 7903
- Suitable for carriageway and fast moving traffic applications
- AMP™ anti-movement technology frames
- Non-rock captive hinged for stability and silent operation
- Pedestrian & cycle friendly products available
- Ductile iron to ISO 1083 for improved weight to strength ratio
- Black coated finish

Options:

- Right hand hinging available on selective products, please enquire.
- Locking with standard bolts

Standard Sizes

Code	Legacy Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	HA 102	Waterway (cm ²)	Gully
SEVERN 3138 S#	KD51D	380 x 310	480 x 370	100	-	876	375
SEVERN PROMENADE 3138 S*#	KD51DP*	380 x 310	560 x 410	100	-	370	375
SEVERN 3550 S	KD52D	495 x 345	690 x 485	100	-	1140	450
SEVERN 3743 S	KD50DNN	370 x 430	496 x 610	100	R	1200	450
SEVERN 3743 H	KD50D6N	370 x 430	496 x 610	150	R	1200	450
SEVERN DISHED 420 S**	KD502	420 x 420	585 x 490	100	-	1216	450
SEVERN 450 S	KD53D	450 x 450	640 x 540	100	R	1425	450
SEVERN 450 H	KD53D-6	450 x 450	640 x 540	150	R	1425	450
SEVERN 4560 S	KD54D	600 x 450	790 x 540	100	Q	1815	450
SEVERN DISHED 4575**	KD57D**	750 x 450	940 x 540	150	Q	2262	450

*Pedestrianised

**Dished

#Not CD 534 compliant

Standard Sizes

Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	HA 102	Waterway (cm ²)	Gully	Type
BUFFALO	375 x 430	530 x 525	100	-	1140	450	
FORTH 100	446 x 443	592 x 530	100	-	1139	450	
PROMENADE 100	446 x 443	592 x 530	100	-	1139	450	Pedestrianised