


LIBERTY DRAIN™ 150

150 mm Wide Innovative Channel Drainage



LIBERTY DRAIN™ 150



D 400 Grating



F 900 Grating

Features:

- Manufactured to BS EN 1433 class D 400, F 900 as specified
- High quality polypropylene channel base
- Interlocking channel tongue & groove joints
- Smooth internal face for rapid flow rates
- Ductile Iron gratings
- 6 mm Safe-slot gratings (D 400)
- 15 mm Hydro-slot for maximum capacity drainage (F 900)
- 8 point locking per metre
- Galvanised Steel edge rail

Options:

- Stepped Falls
- Integrated 90° turns
- Integrated 'T' junctions

Standard Sizes

Code	Int Width (mm)	Invert Depth (mm)	O/all Width (mm)	O/all Depth (mm)	Loading	Waterway (cm ² per grate)	Weight (kg)
LDD150-6-100	150	122	209	156	D 400	231	21
LDD150-6-150	150	172	209	206	D 400	231	22
LDF150-15-100	150	122	209	156	F 900	383	24
LDF150-15-150	150	172	209	206	F 900	383	24

Sump Unit

Standard Sizes

LDD150-6-400	150	422	209	442	D 400	231	23
LDF150-15-400	150	422	209	442	F 900	383	22