


LIBERTY DRAIN™ 200

200 mm Wide Innovative Channel Drainage



LIBERTY DRAIN™ 200



D 400 Grating



F 900 Grating

Features:

- Manufactured to BS EN 1433 class D 400, F 900 as specified
- High quality polypropylene channel base
- Interlocking channel tongue & groove joints
- Smooth internal face for rapid flow rates
- Ductile Iron gratings
- 6 mm Safe-slot gratings (D 400)
- 15 mm Hydro-slot for maximum capacity drainage (F 900)
- 8 point locking per metre
- Galvanised Steel edge rail

Options:

- Stepped Falls
- Integrated 90° turns
- Integrated 'T' junctions

Standard Sizes

Code	Int Width (mm)	Invert Depth (mm)	O/all Width (mm)	O/all Depth (mm)	Loading	Waterway (cm ² per grate)	Weight (kg)
LDD200-6-100	200	122	259	156	D 400	412	30
LDD200-6-150	200	172	259	206	D 400	412	30
LDD200-6-200	200	222	259	256	D 400	412	31
LDD200-6-300	200	322	259	356	D 400	412	32
LDF200-15-100	200	122	259	156	F 900	505	27
LDF200-15-150	200	172	259	206	F 900	505	28
LDF200-15-200	200	222	259	256	F 900	505	28
LDF200-15-300	200	322	259	306	F 900	505	29

Sump Unit

Standard Sizes

LDD200-6-400	200	422	259	442	D 400	412	28
LDF200-15-400	200	422	259	442	F 900	505	27