

C 250 Drainage Gratings



KD51CP



KD72C



KD71

Features:

- Manufactured to BS EN 124 class C 250
- BSI Kitemarked for third party assurance of quality
- Suitable for carriageway not exceeding 500 mm from kerbside
- AMP™ patented anti-movement technology frames
- Pedestrian & cycle friendly products available
- Captive hinged for easy access and increased security
- Ductile iron to ISO 1083 for improved weight to strength ratio
- Black coated finish

Options:

- Right hand hinging available

Standard Sizes

Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	HA102	Waterway (cm ²)	Weight (kg)	Gully	Type
KD51C	380 x 310	480 x 370	75	S	890	18	375	Hinged
KD51C2L*	360 x 310	460 x 368	75	-	809	13	375	Hinged
KD51CP	380 x 310	480 x 370	75	T	619	20	375	Pedestrian, Hinged
KD51C3D*	390 x 315	499 x 377	75	-	891	17	375	Dished, Hinged
KD50CN	420 x 420	520 x 480	75	R	1229	24	450	Hinged
KD41C	445 x 445	500 x 500	75	-	1107	34	450	Double Tri
KD70**	225 x 225	285 x 263	50	-	237	11	228	Yard, Flat
KD71**	225 x 225	285 x 263	50	-	215	10	228	Yard, Dished
KD72C**	325 x 325	385 x 365	75	T	530	16	304	Yard, Flat
KD73C**	325 x 325	385 x 365	75	-	495	16	304	Yard, Dished

*Locked as standard

**Rear Hinged as standard