

## SPECIFICATION FOR DRIZIT® EXTREME 240GSM MAINTENANCE ROLLS



	MRG24SL001BG	LRG24SL001BG
<b>Size</b>	50cm x 40m	100cm x 40m
<b>Perforations</b>	Across every 40cm	Across every 40cm Along at 50cm
<b>Colour</b>	Grey	Grey
<b>Pack Quantity</b>	1	1
<b>Pack Wt (gross)</b>	4.8 kg	9.6 kg
<b>Pack Size</b>	50 x 35 x 35 cm	100 x 35 x 35 cm
<b>Sorbency (pack)</b>	43 - 86 litres	86 - 173 litres

*Sorbency: Lower figure test method to BS 7959-1:2004 using water. Higher figure based on high viscosity liquid with no drain.*

- Composition:** >99.5% Polypropylene, <0.5% dye  
Meltblown, ultrasonically bonded, spunbond laminated on one side
- Basis Wt:** 17gsm spunbond 223gsm meltblown
- Pack Type:** Bag
- Compatibility:** May be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, **with the exception of strong oxidising agents.**  
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)  
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.  
This product is non-toxic to users and to aquatic life.  
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018