



Ø1260 x 2135mm SINGLE PIECE
ROTATIONALLY MOULDED HDPE SUMP

INLET	Ø110MM SOCKET
OUTLET	Ø110MM SPIGOT
NOMINAL CAPACITY	1800 LITRE
SLUDGE/GREASE CAPACITY	800/450 LITRE

MATERIAL SPECIFICATIONS

MANUFACTURED WEIGHT	75 KG
FEATURES & BENEFITS	HIGH STIFFNESS AND HARDNESS EXCELLENT IMPACT STRENGTH UV10 STABILISED

SEPARATES AND RETAINS FATS, OILS AND GREASE (FOG's)

Please Note: All passive grease traps require regular service and removal of accumulated controlled waste for environmental disposal by registered waste carriers

© Oaklands Environmental Ltd 2014.
We reserve the right to change specification without prior notice in line with our policy of continuous development.
www.oaklandsenvironmental.com
PART OF THE OAKLANDS GROUP OF COMPANIES

REV	DETAIL	DATE	DRAWN
1	Address updated	01/01/09	gf
2	Dip pipe added	01/05/10	gf
3	Specification added	13/10/11	gf
4	Image added	27/06/12	gf
5	Adapted to OE1220 sump	16/04/14	gf
6	Volumes verified	06/10/16	gf

TITLE	GS2 Grease Separator
CUSTOMER	

DRAWING NO	GA1109/08	DATE	11/01/2008	DRAWN	gf
THIRD ANGLE PROJECTION				SCALE	NOT TO SCALE
				SHEET	1 of 1
TOLERANCE +/- 2%				REV	5