



INTEGRITY™ KD500

Technical Sheet

Hinged Gully Grating and Frame

Designed to Suit a 450mm Dia Gully Pot



Material

EN GJS 500-7 Iron
ISO 1083 / EN1563


CD534
Compliant

INTEGRITY™ by EJ, a new gully grating and frame range: completely re-imagined, and re-engineered. The range not only fully meets the requirements of BS EN 124-2:2015 but also incorporates significant design advantages over competing products. Unique to this fully-featured product is the enhanced flared frame design that provides maximum support when fitted over a 450mm diameter gully pot.


Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	EN 124	Description	Waterway (cm ²)	Gully Pot Ø (mm)
KD500	430 x 370	580 x 483	100	D 400	Ductile Iron, Grating & Frame.	1037	450
KD500-6	430 x 370	580 x 483	150	D 400	Ductile Iron, Grating & Frame.	1037	450

Features


- EN 124-2:2015 Load Class D400
- BSI Kitemarked
- Locking Available (Retro Drill & Tap Frame)
- Minimum Mortar Line Indicator
- AMP™ Anti-Movement Technology
- V-seating wedge design - Non-Rock, Silent & Stable
- Captive End Hinged Grating
- Enhanced Base Frame For Maximum Support
- 4L® Raised Anti-Slip Pattern



Designed To Suit A
Ø450mm Gully Pot




1037cm²
Waterway Area



Enhanced Base
Frame For
Maximum Support



Minimum Mortar
Line Indicator



V-Seating Wedge
Design for Non-Rock