


Platin Garden Comfort Package



Platin Garden Comfort package

- Simple & quick to install
- Submersible pump supplies harvested rainwater on demand to external taps, internal and external hose connection boxes
- Water can be extracted using an internal and/or external hose connection box for standard irrigation purposes

Scope of supply

- ① Underground tank (choice of tanks available, sizes vary according to property type)
- ② Telescopic lid (choice of telescopic lid available, depending on tank location)
- ③ Filter (Basket filter supplied in accordance with type of tank)
- ④ Submersible pump with floating water intake
- ⑤ Internal hose connection box
- ⑥ External hose connection box

Supplied by others

- ⑦ 100mm diameter duct pipe to contain; power cable for pump
- ⑧ 100mm diameter drainage pipe connected from downpipes to the inlet at the top of the tank (all downpipes brought into one pipe for connection to the filter)
- ⑨ 100mm diameter pipe for overflow from the tank to mains drainage network or soakaway

Dimensions/weight	1,500 litres (400 US gallons)	3,000 litres (800 US gallons)	5,000 litres (1,350 US gallons)	7,500 litres (1,980 US gallons)
Length (l)	2,100mm (82.6")	2,450mm (96.5")	2,890 (113.8")	3,600 (141.7")
Width (w)	1,250mm (49.2")	2,100mm (82.7")	2,300mm (90.6")	2,250mm (88.6")
Height of tank shoulder (h)	700mm (27.5")	735mm (28.9")	950mm (37.4")	1250mm (49.2")
Height of dome collar (hd)	315mm (12.4")	315mm (12.4")	315mm (12.4")	315mm (12.4")
Ø tank dome (d)	800mm (31.5")	800mm (31.5")	800mm (31.5")	800mm (31.5")
Weight	80kg	170kg	240kg	360kg

