

BEACON AND SOUNDER

Flashing beacons and sounder beacons can be used alongside our range of alarms to provide a visual and/or audible warning.

Flashing Beacon

- Ingress Protection: IP66
- Housing material: UL94V0 & 5VA FR ABS
- Housing colour: RAL3000 Red, RAL7038
- Grey and White
- Lens material: PC
- Fixings: Stainless Steel
- Operating temp: -25° to +55°C
- Storage temp: -40° to +70°C
- Relative humidity: 90% at 20°C
- Energy: 5 Joules (5Ws)
- Flash rate: 1Hz (60 fpm) DC units: Optionally 1.5Hz & double strike
- Peak Candela: 500,000 cd - calc. from energy (J)
- Effective candela: 250 cd - calc. from energy (J)
- Peak Candela: 86,935 cd* - measured ref. to I.E.S.
- Effective candela: 200 cd* - measured ref. to I.E.S.
- Terminals: 0.5 to 4.0mm² cables.
- Lens colours: Amber, Blue, Clear, Green, Red, Yellow
- Tube life: Emissions are reduced to 70% after 8 million flashes

Sounder Beacon

- IP55 rated
- Can be wired with sounder and beacon operating separately or together
- 3 alarm stage options
- Volume control
- Automatic synchronisation
- UL94V0 flame retardant ABS case and polycarbonate lens
- Xenon tube life: >5million flashes
- Cable entries: 2 x M20 clearance gland entries in side & back
- Terminals: 0.5 to 1.5mm² cables.
- Operating temp: -25 to +55°C
- Storage temp: -40 to +70°C
- Relative humidity: 90% at 20°C.
- Weight : DC: 0.95kg AC:1.20kg



Revision Date: 07/11/2018